



## Product Specification and Technical Data

**PRODUCT: BG FRE•IT**

**PART NO.: 435**

| <b>TEST DATA:</b> | <b>Test</b>                                       | <b>ASTM Test Method</b> | <b>Typical Test Results</b> |
|-------------------|---|-------------------------|-----------------------------|
|                   | Specific Gravity (H <sub>2</sub> O = 1) . . . . . | D 1298 . . . . .        | 0.78                        |
|                   | Boiling Point . . . . .                           | D 86 . . . . .          | 149°C (300°F)               |
|                   | Flash Point, COC . . . . .                        | D 92 . . . . .          | 43°C (110°F)                |
|                   | Solubility in Water . . . . .                     |                         | Negligible                  |
|                   | Vapor Pressure, psig @ 21°F (70°F) . . . . .      |                         | <5                          |
|                   | Net Weight, oz. (grams) . . . . .                 |                         | 11.75 (333)                 |
|                   | Volume, fl. oz. . . . .                           |                         | 15.74                       |

**DESCRIPTION:** BG FRE•IT is a superior multi-purpose aerosol product developed for use in automotive, farm, home and recreational applications. It is formulated with special solvents to quickly penetrate and rapidly free frozen bolts, fasteners, tools, and rusted or corroded metal parts. BG FRE•IT seeks out and displaces moisture to stop irritating squeaks, and smooths operation of moving parts. BG FRE•IT is recommended for use on firearms, fishing reels, sliding doors, locks, window cranks, hinges, zippers, television tuners, switches, relays, verniers, dies, tools, ignition systems, and literally hundreds of other uses. BG Fre-it is equipped with a unique 360-degree valve and actuator that permits application from any angle in a stream or a fine mist. BG Fre-it will not harm paints, plastics or rubber when used as directed.

**USAGE:** Spray on surfaces as needed and wait a few minutes. No need to wipe off. To start wet engine, spray on electrical parts and wait for moisture to be displaced.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.