



Product Specification and Technical Data

PRODUCT: BG Hi-LOW30
SAE 0W-30 Full Synthetic Engine Oil

PART NO.: 730

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D 287	35.4
	Specific Gravity @ 15.6°C (60°F)	D 1298	0.8478
	Density,		
	U.S. lbs./gal. @ 15.6°C (60°F)	D 1250	7.068
	Viscosity, cSt @ 40°C (104°F)	D 445	60.24
	Viscosity, cSt @ 100°C (212°F)	D 445	11.03
	Viscosity Index	D 2270	178
	Flash Point, COC	D 92	212°C (414°F)
	Viscosity, cP @ -35°C (-31°F)	D 5293	5621
	Pour Point	D 97	-45°C (-43°F)
	Noack Volatility, % Loss	DIN 5181	11.23
	Color	D 1500	L3.0
	Color	Visual	Brown

DESCRIPTION: BG Hi-LOW30 is a revolutionary full synthetic engine oil utilizing the most shear stable polymer technology available. It flows immediately to lubricate vital engine components and prevent wear even at very low temperatures. It resists thermal oxidation, evaporation, viscosity increase (thickening) and provides a long drain life of 15,000 miles (24,000 km) or one year. BG Hi-LOW30 is formulated with premium levels of detergent/dispersants to keep the engine clean.

USAGE: BG Hi-LOW30 is designed for passenger cars, vans and light trucks requiring API SN and preceding engine oil. It is recommended for use in vehicles factory-filled with a full synthetic 0W-20, 5W-20, 0W-30, 5W-30 or 10W-30 engine oil. Use in accordance with engine manufacturer’s recommendations.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.