



Product Specification and Technical Data

PRODUCT: BG SAE 10W-30 Synthetic Blend Engine Oil

PART NO.: 775

TEST DATA: Test	ASTM Test Method	Typical Test Results
API Gravity @ 15.6°C (60°F)	D 287	31.4
Specific Gravity @ 15.6°C (60°F).	D 1298	0.8687
Density,		
U.S. lbs./gal. @ 15.6°C (60°F).	D 1250	7.242
Flash Point, COC	D 92	213°C (416°F)
Viscosity, cSt @ 40°C (104°F).	D 445	69.74
Viscosity, cSt @ 100°C (212°F)	D 445	11.34
Viscosity Index	D 2270	156
Viscosity, cP @ -30°C (-22°F)	D 5293	3427
Noack Volatility, % Loss	DIN 5181	12.60
Pour Point	D 97	-40°C (-40°F)
Total Base Number, mg KOH/g	D 2896	8.5
Color	D 1500	3.0
Color	Visual	Amber

DESCRIPTION: BG SAE 10W-30 Synthetic Blend Engine Oil delivers excellent engine protection for all operating climates. It lubricates and cools internal engine surfaces and prevents wear in gasoline engines. It flows at temperature as low as -40°F (-40°C) and resists evaporation and thickening.

USAGE: BG SAE 10W-30 Synthetic Blend Engine Oil is designed for passenger cars, vans and light trucks requiring API SN and preceding engine oil. Use in accordance with engine manufacturer’s recommendations.

BG Products, Inc., accepts no liability for excessive use or misuse of this product.